Product data sheet Characteristics

EPH0400421

Asfora - 1pole 2way switch -10AX screwless, IP44 white





Main

Range	Asfora
Product or component type	Switch
Device presentation	Complete product
Load type	Load for energy saving lamps with ballast: 100 W
Colour tint	White
Type of packing	Flow-pack

Complementary

Device mounting	Flush	
Switch function	1-pole 2-way	
Number of rocker	1.0	7
Power range	2300 W	
Rated current	10 AX at 250 V AC	
Connections - terminals	Screwless terminals	
Number of cables	2 cable(s) 2.5 mm²	 [
Cable stiffness	Flexible Rigid Solid stranded	, , ,
Wire stripping length	13.0 mm	
Material	ABS (acrylonitrile butadiene-styrene)	7
Surface finish	Glossy	
Conductor material	Copper	
Fixing mode	Screws or claws5170 mm	
Height	83 mm	
Width	83 mm	
Depth	43.0 mm	
Projecting depth	15 mm	

Net weight	0.0858 kg
Environment	
Standards	IEC 60669-1
Product certifications	TSE
	VDE NF
Quality labels	CE
addin, idao.o	UKR
IP degree of protection	IP44
Ambient air temperature for operation	-540 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	87.333 g
Package 1 Height	4 cm
Package 1 width	8.3 cm
Package 1 Length	8.3 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.857 kg
Package 2 Height	9.5 cm
Package 2 width	18.5 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Weight	22.534 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Contraction Warranty		
Warranty	18 months	