

Composite 3/4" impact wrench

NK.2000F

- Speed controller.
- 3 tightening torque settings.
- Direction reversal knob.
- Double-hammer mechanism.
- Free speed : 5,500 rpm.
- Recommended dynamic torque : 270 - 1,220 Nm.
- Maximum dynamic torque : 1,500 Nm.
- Guaranteed static torque : 810 Nm.
- Impact rate (per minute) : 1,050.
- Average air consumption : 600 l/min.
- Air inlet thread : 3/8".
- Working pressure : 6.2 bars.



3/4" impact wrench set

NK.1101E


- 15-piece set comprising :
 - 1 impact wrench NK.1000F.
 - 11 impact sockets NK.19A, 21A, 22A, 23A, 24A, 26A, 27A, 28A, 29A, 30A and 32A.
 - 1 extension NK.210A.
 - 1 universal joint NK.240A.
 - 1 sleeve N.610.
 - 3 Rings and 3 locking pins (BA and GA).
- Complete with metal case BT.104 and tray PL.81B.
- ΔΔ : 19.6 kg.



1" impact wrench

NM.1000F

- Speed controller.
- Direction reversal knob.
- Double-hammer mechanism.
- Free speed : 4,400 rpm.
- Recommended dynamic torque : 130-1,650 Nm.
- Maximum dynamic torque : 2,170 Nm.
- Guaranteed static torque : 1500 Nm.
- Impact rate (per minute) : 720.
- Average air consumption : 255 l/min.
- Air inlet thread : 1/2".
- Working pressure : 6.2 bars.



	a	b	c	ΔΔ
	mm	mm	mm	kg
NM.1000F	300	290	205	9,84