



Statut commercial
Arrêt de fabrication :

⚠ Arrêt de fabrication

Main

Product or component type	Contacteur
Device short name	CT
Device application	Control circuit
Poles description	3P
[Ie] rated operational current	40 A AC-7A
Pole contact composition	3 NO
Network type	AC
Control type	Remote control
[Uc] control circuit voltage	220/240 V AC 50 Hz

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	400 V AC 50 Hz
Maximum power	10.4 W at 400 V AC
Control signal type	Maintained
Local signalling	Color indicator
Hold-in power consumption in VA	6.5 VA
Inrush power in VA	53 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6
Height	81 Mm
Width	54 Mm
Depth	60 Mm
Colour	Grey
Mechanical durability	1000000 Cycles
Electrical durability	100000 Cycles IEC/EN 61095 40 A 50 Hz AC-7A 30000 Cycles IEC/EN 61095 50 Hz AC-7B 30000 Cycles IEC/EN 61095 50 Hz AC-7C 100000 Cycles EN/IEC 60947-4-1 50 Hz AC-1 30000 Cycles EN/IEC 60947-4-1 50 Hz AC-3 30000 Cycles EN/IEC 60947-4-1 50 Hz AC-5a 30000 Cycles EN/IEC 60947-4-1 50 Hz AC-5b

Connections - terminals	Control circuit: tunnel type terminals2 cable(s) 2.5 mm ² flexible Control circuit: tunnel type terminals2 cable(s) 1.5 mm ² rigid Power circuit: tunnel type terminals2 cable(s) 10 mm ² flexible Power circuit: tunnel type terminals1 cable(s) 25 mm ² rigid
Product compatibility	Time delay Interference filter Auxiliary contact Mixed control: impulse/latched
Compatibility code	CT

Environment

Standards	IEC/EN 61095
Product certifications	IMQ EAC CEBEC CCC VDE
Noise level	30 DB
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...60 °C

Packing Units

Package 1 Weight	0.340 Kg
Package 1 Height	1.100 Dm
Package 1 width	0.570 Dm
Package 1 Length	1.230 Dm

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. - Block**

La référence 15967 peut être remplacée par l'un des produits suivants :



A9C20843

contactor iCT - 3 poles - 3 NO - 40 A - 220..240 V AC

Qté 1

Raison de la substitution : Fin de vie. | Date de substitution : 01 janv. 2011 |



A9C20843

contactor iCT - 3 poles - 3 NO - 40 A - 220..240 V AC

Qté 1

Raison de la substitution : Fin de vie. | Date de substitution : 01 janv. 2011 |



A9C20843

contactor iCT - 3 poles - 3 NO - 40 A - 220..240 V AC

Qté 1

Raison de la substitution : Fin de vie. | Date de substitution : 01 janv. 2011 |



A9C20843

contactor iCT - 3 poles - 3 NO - 40 A - 220..240 V AC

Qté 1

Raison de la substitution : Fin de vie. | Date de substitution : 31 déc. 2017 |
