



Main

Range	Domae
Product or component type	Residual current circuit breaker (RCCB)
Device short name	RCCB
Poles description	2P
Earth-leakage protection class	Type AC

Complementary

Neutral position	Left
Device location in system	Outgoer
[In] rated current	40 A
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz conforming to IEC 61008
Residual current tripping technology	Electromechanical
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Rated conditional short-circuit current	3 KA 40 A
Control type	Toggle
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	81 Mm
Width	36 Mm
Depth	76 Mm
Connections - terminals	Tunnel type terminals 1...25 mm ² flexible

Environment

Standards	IEC 61008
Tropicalisation	2 conforming to IEC 61008
Operating altitude	2000 m

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins