



Main

Product or component type	Add-on residual current devices	
Device short name	Vigi NG125	
Poles description	4P	
[In] rated current	63 A	
Network type	AC	
Earth-leakage sensitivity	300 MA	
Earth-leakage protection time delay	Selective	
Earth-leakage protection class	Туре А	

Complementary

Complementary		
Device location in system	Outgoer	
Network frequency	50/60 Hz	
[Ue] rated operational voltage	230415 V AC 50/60 Hz	
Residual current tripping technology	Voltage independent	
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2	
[Uimp] rated impulse withstand voltage	8 KV conforming to IEC 60947-2	
Mounting support	35 mm symmetrical DIN rail	
Electrical connection to mcb	By screws	
9 mm pitches	9	
Height	118 Mm	
Width	189 Mm	
Depth	81 Mm	
Net weight	0.45 Kg	
Electrical durability	10000 Cycles conforming to IEC 60947-2	
Connections - terminals	Tunnel type terminals 135 mm² flexible Tunnel type terminals 1.550 mm² rigid	
Wire stripping length	20 Mm	
Tightening torque	3.5 N.M	

Environment

Standards	IEC 60947-2	
IP degree of protection	IP40 conforming to IEC 60947-2	
Pollution degree	3 conforming to IEC 60947-2	
Electromagnetic compatibility	8/20 μs impulse withstand, 5000 A conforming to IEC 60947-2	
Tropicalisation	2 conforming to IEC 60068-1	

Relative humidity	95 % at 55 °C	
Operating altitude	2000 m	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	509 G	
Package 1 Height	9.5 Cm	
Package 1 width	13.5 Cm	
Package 1 Length	26 Cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	8	
Package 2 Weight	4.836 Kg	
Package 2 Height	30 Cm	
Package 2 width	30 Cm	
Package 2 Length	40 Cm	
Offer Sustainability		
Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Circularity Profile	☑ End Of Life Information	
WEEE	The product must be disposed on European Union markets following speci- fic waste collection and never end up in rubbish bins	

Product Life Status :	Commercialised	

18 months



Contractual warranty

Warranty