Product data sheet Characteristics

A9N18570

Vigi C120 - earth leakage add-on block - 4P - 300 mA - class AC





Main

TVI CALL		
Product or component type	Add-on residual current devices	
Device short name	Vigi C120	
Poles description	4P	
[In] rated current	125 A	
Network type	AC	
Earth-leakage sensitivity	300 mA	:
Earth-leakage protection time delay	Instantaneous	
Earth-leakage protection class	Type AC	

Complementary

Device location in system	Outgoer	ì
Network frequency	50/60 Hz	-
[Ue] rated operational voltage	230415 V AC 50/60 Hz	- 9
Residual current tripping technology	Voltage independent	- \$
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-1	<u>و</u> . –
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2	- 5
Mounting mode	Clip-on	-titite
Mounting support	35 mm symmetrical DIN rail	_ 2
Electrical connection to mcb	By screws	_ 6
9 mm pitches	10	-
Height	95 mm	
Width	198 mm	u
Depth	73 mm	_ citato
Net weight	0.58 kg	_ a
Colour	White	- 5
Mechanical durability	20000 cycles	- E
		~

Connections - terminals	Tunnel type terminals 135 mm² flexible Tunnel type terminals 150 mm² rigid
Wire stripping length	15 mm
Tightening torque	3.5 N.m

Environment

Standards	EN 61009
IP degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-2
Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-4060 °C

Packing Units

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	674 g
Package 1 Height	9.2 cm
Package 1 width	13.5 cm
Package 1 Length	25.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	5.896 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	64
Package 3 Weight	55.668 kg
Package 3 Height	75 cm
Package 3 width	60 cm
Package 3 Length	80 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

	•	
Warranty		18 months