



⚠ To be discontinued

Commercial status

To be discontinued on: 15 December 2020

Main

Range	Acti 9
Product name	Acti 9 iSW
Product or component type	Switch disconnecter
Device short name	ISW
Device application	Isolation Control
Poles description	4P
Utilisation category	AC-22A conforming to EN 60947-3 AC-22A conforming to IEC 60947-3
Suitability for isolation	Yes conforming to EN 60947-3 Yes conforming to IEC 60947-3

Complementary

Network type	63 A at 415 V AC 50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
Standards	500 V AC 50/60 Hz conforming to IEC 60947-3
Standards	6 kV conforming to EN 60947-3 6 kV conforming to IEC 60947-3
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Standard
Colour	White
Connections - terminals	Tunnel type terminals - <= 50 mm ² - rigid Tunnel type terminals - <= 35 mm ² - flexible Tunnel type terminals - <= 35 mm ² - flexible with ferrule

Environment

Standards	IEC 60947-3
-----------	-------------

IP degree of protection	IP4
Pollution degree	3 conforming to IEC 60947-3
Tropicalisation	2

Packing Units

Package 1 Weight	0.299 kg
Package 1 Height	0.780 dm
Package 1 width	0.720 dm
Package 1 Length	0.850 dm

Contractual warranty

Warranty	18 months
----------	-----------

A9S60463 is replaced by:



switch-disconnector A9S65463

switch disconnector iSW - 4P - 63 A - 415 V

Qty 1

Reason for Substitution: End of life | Substitution date: 01 January 2017