



### Main

Range	Asfora
Product or component type	Dimmer
Device presentation	Complete product
Load type	230 V AC halogen lamp: 40...600 W 230 V AC incandescent lamp: 40...600 W Low voltage halogen lamp with ferromagnetic transformer: 40...600 W
Colour tint	White
Type of packing	Box

### Complementary

Device mounting	Flush
Switch function	1-pole 2-way
Dimmer control	Rotary push type
Dimmer application	Ohmic load Inductive load
Protection type	Fuse protection
Associated fuse rating	6.3 A
[Ue] rated operational voltage	230 V AC 50 Hz
Connections - terminals	Pillar terminals
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable stiffness	Rigid Flexible
Wire stripping length	8 mm
Material	ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame ABS (acrylonitrile butadiene-styrene): knob
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws 53...78 mm
Height	83 mm
Width	83 mm
Depth	49 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Projecting depth	20 mm
Net weight	0.111 kg

## Environment

Product certifications	SEMKO UKR TSE FIMKO NEMKO VDE GOST
Quality labels	CE
IP degree of protection	IP20

## Packing Units

Package 1 Weight	111.000 g
Package 1 Height	83.000 mm
Package 1 width	126.000 mm
Package 1 Length	62.000 mm

## Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------