



ⓘ Discontinued

Main

Product or component type	Add-on residual current devices
Device short name	Vigi C60
Poles description	2P
[In] rated current	25 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A-SI

Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	220...415 V AC 50/60 Hz
Residual current tripping technology	Voltage dependent
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
Mounting support	35 mm symmetrical DIN rail
Electrical connection to mcb	By screws
9 mm pitches	3
Height	87 mm
Width	63 mm
Depth	74 mm
Net weight	0.12 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals 0.5...16 mm ² flexible Tunnel type terminals 0.5...25 mm ² rigid
Wire stripping length	14 mm
Tightening torque	2 N.m

Environment

Standards	IEC 60947-2
-----------	-------------

Pollution degree	3 conforming to IEC 60947-2
Tropicalisation	2 conforming to IEC 60947-2
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C


Packing Units

Package 1 Weight	0.143 kg
Package 1 Height	0.800 dm
Package 1 width	0.760 dm
Package 1 Length	0.950 dm

Contractual warranty

Warranty	18 months
----------	-----------

26747 is replaced by the following product range:



Vigi for Acti9 iC60

Residual current add-on devices up to 63 A for Acti9 iC60 Miniature Circuit Breakers

Simple to install and ideal for all industrial and commercial buildings, the residual current add-on devices for Acti9 iC60 provide you with leakage protection whilst ensuring a greater continuity of service

Reason for Substitution: End of life | Substitution date: 31 December 2013