



Main

| | |
|--------------------------------|---|
| Range of product | NSX100...250 |
| Product or component type | Trip unit |
| Range compatibility | Compact NSX100 Compact NSX160 |
| Device application | Motor |
| Poles description | 3P |
| Protected poles description | 3t |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Trip unit name | MA |
| Trip unit technology | Magnetic |
| Trip unit protection functions | I |
| Protection type | I : for short-circuit protection (magnetic) |
| Trip unit rating | 25 A at 65 °C |

Complementary

| | |
|---|-----------------------|
| Mounting mode | Fixed |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Instantaneous pick-up adjustment type li | Adjustable 9 settings |
| [li] instantaneous pick-up adjustment range | 6...14 x In |

Environment

| | |
|------------------------|--------------------------|
| Standards | UL 508 EN/IEC 60947-2 |
| Product certifications | Marine EAC CCC |

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

Packing Units

| | |
|------------------|-----------|
| Package 1 Weight | 0.393 kg |
| Package 1 Height | 6.600 cm |
| Package 1 width | 9.900 cm |
| Package 1 Length | 11.500 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| RECh Regulation | RECh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|