



### Main

Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	Compact NSX250 circuit breaker Compact NSX160 circuit breaker Easypact CVS100 circuit breaker Easypact CVS160 circuit breaker
Poles description	4P
[In] rated current	160 A 100 A
Earth-leakage add-on module name	MH
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Adjustable 5 settings
Earth-leakage sensitivity	0.03 A 0.3 A 1 A 3 A 10 A
Residual earth-leakage time delay adjustment type	Adjustable 4 settings
[Δt] residual earth-leakage time delay adjustment	0 ms 150 ms 310 ms 60 ms

### Complementary

Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms
Oversvoltage category	Class II

## Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.304 kg
Package 1 Height	13.5 cm
Package 1 width	14.5 cm
Package 1 Length	17 cm
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Weight	16.161 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Weight	76.936 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------