



Main

Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	Compact NSX EasyPact CVS PowerPact Multistandard
Voltage release type	Shunt trip release
[Uc] control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz

Complementary

Control signal type	Impulse Maintained
Impulse duration	≥ 20 ms
Threshold tripping voltage	0.7... 1.1 x U_n opening
Supply inrush power	10 VA
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Screw terminal 0... 1.5 mm ²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	127 g
Package 1 Height	4 cm
Package 1 width	6.3 cm
Package 1 Length	8.2 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.36 kg
Package 2 Height	9.2 cm

Package 2 width	14.8 cm
Package 2 Length	22.4 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	8.65 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------