Product datasheet Characteristics

LV429410

undervoltage release MN - 24 V DC





Main

Device short name	MN	
Product or component type	Voltage release	
Device application	Control	
Range compatibility	Compact NSX EasyPact CVS PowerPact Multistandard	
Voltage release type	Undervoltage release	
[Uc] control circuit voltage	24 V DC	

Complementary

· · · · · · · · · · · · · · · · · ·		
Threshold tripping voltage	0.350.7 x Un opening 0.85 x Un closing	
Supply holding power	5 W	
Supply inrush power	10 W	
Mounting mode	Fixed	
Response time	50 ms	
Auxiliary connection terminal	Screw terminal01.5 mm²	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	127 g	
Package 1 Height	6.2 cm	
Package 1 width	4 cm	
Package 1 Length	8.1 cm	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Weight	1.333 kg	

Package 2 Height	15 cm
Package 2 width	9 cm
Package 2 Length	23 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	8.49 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information		
Environmental Disclosure	Product Environmental Profile		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		

Contractual warranty

Warranty	18 months		