



### Main

Device short name	Motor mechanism module with SDE adaptor
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	Compact NSX circuit breaker Compact NSX DC circuit breaker circuit breaker
Product compatibility	PowerPact J-Frame PowerPact H-Frame
[In] rated current	250 A
[Uc] control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz

### Complementary

Control type	Standard
Control signal type	Maintained Impulse
Mounting mode	Fixed
Response time	< 600 ms (opening) < 80 ms (closing)
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	1 to 3 padlocks Ø 5 to Ø 8 Padlocking in OFF position

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.384 kg
Package 1 Height	11 cm
Package 1 width	12 cm
Package 1 Length	17 cm
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Weight	21.526 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------