Product data sheet Characteristics

LV432080

trip unit Micrologic 2.3 for Compact NSX 630 circuit breakers, electronic, rating 630A, 3 poles 3d



Range of product	NSX400630	
Product or component type	Control unit	
Range compatibility	Compact NSX630	
Device application	Distribution	
Poles description	3P	-
Protected poles description	3t	
Network type	AC	;
Network frequency	50/60 Hz	
Trip unit name	Micrologic 2.3	:
Trip unit technology	Electronic	
Trip unit protection functions	LSol	
Protection type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection	:
Trip unit rating	630 A at 40 °C	

Complementary

Main		
Range of product	NSX400630	
Product or component type	Control unit	
Range compatibility	Compact NSX630	
Device application	Distribution	
Poles description	3P	
Protected poles description	3t	
Network type	AC	
Network frequency	50/60 Hz	
Trip unit name	Micrologic 2.3	
Trip unit technology	Electronic	
Trip unit protection functions	LSol	
D + # +	L : for overload protection (long time)	
Protection type	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection	
Protection type Trip unit rating	So : for short time short-circuit protection with fixed delay	
Trip unit rating Complementary	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection	
Trip unit rating Complementary Mounting mode	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C	
Trip unit rating Complementary Mounting mode [Ue] rated operational voltage	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C Fixed	
Trip unit rating Complementary Mounting mode [Ue] rated operational voltage Long time pick-up adjustment type Ir	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C Fixed 690 V AC 50/60 Hz	
	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C Fixed 690 V AC 50/60 Hz Adjustable 9 settings	
Complementary Mounting mode [Ue] rated operational voltage Long time pick-up adjustment type Ir [Ir] long time pick-up adjustment range Long time delay adjustment type	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C Fixed 690 V AC 50/60 Hz Adjustable 9 settings 0.91 x lo	
Trip unit rating Complementary Mounting mode [Ue] rated operational voltage Long time pick-up adjustment type Ir [Ir] long time pick-up adjustment range Long time delay adjustment type [Tr] long-time delay adjustment range	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C Fixed 690 V AC 50/60 Hz Adjustable 9 settings 0.91 x lo Fixed 11 s at 7.2 x lr 16 s at 6 x lr	
Trip unit rating Complementary Mounting mode [Ue] rated operational voltage Long time pick-up adjustment type Ir [Ir] long time pick-up adjustment range Long time delay adjustment type [Tr] long-time delay adjustment range	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C Fixed 690 V AC 50/60 Hz Adjustable 9 settings 0.91 x lo Fixed 11 s at 7.2 x lr 16 s at 6 x lr 400 s at 1.5 x lr	
Trip unit rating Complementary Mounting mode [Ue] rated operational voltage Long time pick-up adjustment type Ir [Ir] long time pick-up adjustment range	So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection 630 A at 40 °C Fixed 690 V AC 50/60 Hz Adjustable 9 settings 0.91 x lo Fixed 11 s at 7.2 x Ir 16 s at 6 x Ir 400 s at 1.5 x Ir 20 minutes before and after tripping	

[Tsd] short-time delay adjustment range	0.02 s
Instantaneous pick-up adjustment type li	Fixed
[li] instantaneous pick-up adjustment range	6900 A

Environment

Standards	UL 508 EN/IEC 60947-2
Product certifications	CCC Marine EAC
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C

Packing Units

ge 3 Length	60 cm
ge 3 width	80 cm
ge 3 Height	50 cm
ge 3 Weight	67.84 kg
er of Units in Package 3	40
ype of Package 3	P06
ge 2 Length	60 cm
ge 2 width	40 cm
ge 2 Height	30 cm
ge 2 Weight	15.02 kg
er of Units in Package 2	10
ype of Package 2	S04
ge 1 Length	22 cm
ge 1 width	17.5 cm
ge 1 Height	13.5 cm
ge 1 Weight	1.407 kg
er of Units in Package 1	1
ype of Package 1	PCE
ype of Package 1	PCE

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months