



### Main

Range of product	NSX400...630
Product or component type	Control unit
Range compatibility	Compact NSX630
Device application	Distribution
Poles description	3P
Protected poles description	3t
Network type	AC
Network frequency	50/60 Hz
Trip unit name	Micrologic 5.3 E
Trip unit technology	Electronic
Trip unit protection functions	LSI
Protection type	L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection
Trip unit rating	630 A at 40 °C

### Complementary

Mounting mode	Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz
Long time pick-up adjustment type Ir	Adjustable 9 settings
[Ir] long time pick-up adjustment range	250...630 A
Long time delay adjustment type	Adjustable
[Tr] long-time delay adjustment range	15...400 s at 1.5 x Ir 0.35...11 s at 7.2 x Ir 0.5...16 s at 6 x Ir
Thermal memory	20 minutes before and after tripping
Short-time pick-up adjustment type I <sub>sd</sub>	Adjustable 9 settings
[I <sub>sd</sub> ] short-time pick-up adjustment range	1.5...10 x Ir
Short-time delay adjustment type	Adjustable

[Tsd] short-time delay adjustment range	0...0.4 s I <sup>2</sup> t=off 0.1...0.4 s I <sup>2</sup> t=on
Instantaneous pick-up adjustment type li	Adjustable
[li] instantaneous pick-up adjustment range	1.5...11 x I <sub>n</sub>
Zone selective interlocking ZSI	With
Communication of data	Energy metering Demand current and power Power quality Time-stamped histories and event tables Maintenance indicators Maximeters/minimeters Instantaneous and demand values Protection and alarm settings
Display type	LCD display
Type of measurement	Energy meter
Electrical data recording	Maintenance indicators

## Environment

Standards	EN/IEC 60947-2 UL 508
Product certifications	Marine CCC EAC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.49 kg
Package 1 Height	14 cm
Package 1 width	17.6 cm
Package 1 Length	21.6 cm
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Weight	15.666 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------