



Main

Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Range compatibility	Compact NS630b...1600 Compact NS1600b...3200 Compact INS Compact INSE Compact INSJ Compact INV Compact NG Compact NR Compact NSX EasyPact CVS
Offer type	C5 C4
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-make Early-break
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 220/240 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 380/440 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 480 V AC 50/60 Hz AC-12: 6 A at 660/690 V AC 50/60 Hz AC-15: 0.1 A at 660/690 V AC 50/60 Hz AC-15: 1.5 A at 480 V AC 50/60 Hz AC-15: 2 A at 380/440 V AC 50/60 Hz AC-15: 4 A at 220/240 V AC 50/60 Hz AC-15: 5 A at 110 V AC 50/60 Hz AC-15: 6 A at 24 V AC 50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

AC-15: 6 A at 48 V AC 50/60 Hz
 DC-12: 0.3 A at 250 V DC
 DC-12: 0.6 A at 110 V DC
 DC-12: 2.5 A at 48 V DC
 DC-12: 6 A at 24 V DC
 DC-14: 0.03 A at 250 V DC
 DC-14: 0.05 A at 110 V DC
 DC-14: 0.2 A at 48 V DC
 DC-14: 1 A at 24 V DC

Minimum load	100 mA at 24 V
Width	1 cm
Accessory / separate part category	Spare part for Compact NS630b...1600 Spare part for Compact NS1600b...3200

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	24 g
Package 1 Height	2 cm
Package 1 width	8.3 cm
Package 1 Length	8.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	246 g
Package 2 Height	11 cm
Package 2 width	3 cm
Package 2 Length	15 cm
Unit Type of Package 3	S03
Number of Units in Package 3	300
Package 3 Weight	7.8 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

RECh Regulation	REACH Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------