



### Main

Device short name	Carriage switch
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	MasterPact NT Masterpact NW Compact NS630b...1600
Offer type	C4
Signal contacts composition	1 NO/NC

### Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Connected position Test position Disconnected position
Mounting mode	Drawout
[I <sub>e</sub> ] rated operational current	AC-12: 6 A at 690 V AC 50/60 Hz AC-12: 8 A at 240 V AC 50/60 Hz AC-12: 8 A at 380 V AC 50/60 Hz AC-12: 8 A at 480 V AC 50/60 Hz DC-12: 0.3 A at 250 V DC DC-12: 0.8 A at 125 V DC DC-12: 2.5 A at 24/48 V DC
Minimum load	100 mA at 24 V
Accessory / separate part category	Spare part for Masterpact NT Spare part for Masterpact NW Spare part for Compact NS630b...1600

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20 g
Package 1 Height	0.9 cm
Package 1 width	4.7 cm

Package 1 Length	5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	100
Package 2 Weight	3 kg
Package 2 Height	19 cm
Package 2 width	7 cm
Package 2 Length	37 cm
Unit Type of Package 3	S03
Number of Units in Package 3	600
Package 3 Weight	12.4 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

### Offer Sustainability

RECh Regulation	<a href="#">REACH Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)

### Contractual warranty

Warranty	18 months
----------	-----------