



Main

| | |
|---------------------------|----------------------|
| Range of product | Harmony XAC |
| Product or component type | Head for push-button |
| Component name | XACA |

Complementary

| | |
|---------------------------------------|--|
| Marking | Unmarked |
| Operator additional information | Booted |
| Cap/Operator or lens colour | White |
| Product compatibility | XACA.. |
| Mounting location | Front of enclosure |
| Sale per indivisible quantity | 10 |
| Standards | CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60204-32 UL 508 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 100 gn conforming to IEC 60068-2-27 |
| Overvoltage category | Class II conforming to IEC 61140 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 50102 |
| Net weight | 0.01 kg |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.009 kg |
| Package 1 Height | 0.300 dm |
| Package 1 width | 1.100 dm |
| Package 1 Length | 1.000 dm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

| | |
|----------------------------|---|
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|