



Statut commercial

Arrêt de fabrication :

⚠ Arrêt de fabrication

Main

Product or component type	Residual current circuit breaker (RCCB)
Device short name	ID RCCB
Poles description	2P
Neutral position	Left
[In] rated current	40 A
Network type	AC
Earth-leakage sensitivity	300 MA
Earth-leakage protection time delay	Selective
Earth-leakage protection class	Type A-SiE
Rated breaking and making capacity	Im = 630 A
Rated conditional short-circuit current	Inc 10 kA 40 A

Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz conforming to IEC 61008
Residual current tripping technology	Electromechanical
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60947-3
Control type	Toggle
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	81 Mm
Width	36 Mm
Depth	75 Mm
Net weight	0.23 Kg
Colour	Grey
Mechanical durability	20000 Cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminals1...25 mm ² flexible Tunnel type terminals1...35 mm ² rigid
Wire stripping length	15 Mm
Tightening torque	3.5 N.M

Environment

Standards	IEC 60947-1 IEC 60947-3 IEC 61008
Tropicalisation	2 conforming to IEC 61008
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...40 °C
Ambient air temperature for storage	-40...60 °C

Packing Units

Package 1 Weight	0.194 Kg
Package 1 Height	0.850 Dm
Package 1 width	0.400 Dm
Package 1 Length	0.950 Dm

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. - Block**