



❗ Discontinued

## Main

Range	Exiway
Product name	Luxa
Product or component type	Emergency light fitting
Device application	Lighting
Function	Standard
Supply	Non-maintained
Colour	White
Light source	Fluorescent tube G5 8 W
Light source colour	White
Cover type	Transparent
Number of batteries	1 x 8.4 V 1.5 Ah Ni-Cd (Nickel-Cadmium)
Wiring device additional information	Adaptable exit sign Personalized with coloured frames Can be inhibited with rest mode via Teleur range of remote controls

## Complementary

[Ue] rated operational voltage	200...230 V AC/DC 50 Hz
Power consumption in VA	6.5 VA
Electrical insulation class	Class II
Autonomy	1 h
Charging time	12 h
Luminous flux	Maintained mode: 370 lm
Material	Plastic: housing Plastic: cover
Device mounting	Surface ceiling Electrified track Flush false ceiling Flush wall Hanging ceiling

	Surface wall
Height	135 mm
Width	348 mm
Depth	58 mm
Net weight	1.1 kg
Market segment	Small commercial

## Environment

IP degree of protection	IP42
IK degree of protection	IK06
Ambient air temperature for operation	0...40 °C
Fire resistance	850 °C
Standards	EN 60695-2-10 EN 60598-2-22 IEC 695-2-1 IEC 50-11

## Packing Units

Package 1 Weight	1.065 kg
Package 1 Height	0.720 dm
Package 1 width	1.380 dm
Package 1 Length	3.820 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------