



Main

Device short name	4 OF
Product or component type	Auxiliary contact
Range compatibility	Masterpact NW
Signal contacts composition	4 NO/NC

Complementary

Auxiliary contacts type	Standard Low level
Mounting mode	Drawout
[Ie] rated operational current	AC-12: 10 A at 240/380 V AC 50/60 Hz (standard) AC-12: 10 A at 480 V AC 50/60 Hz (standard) AC-12: 3 A at 380 V AC 50/60 Hz (low level) AC-12: 6 A at 24/48 V AC 50/60 Hz (low level) AC-12: 6 A at 240 V AC 50/60 Hz (low level) AC-12: 6 A at 690 V AC 50/60 Hz (standard) DC-12: 10 A at 125 V DC (standard) DC-12: 10 A at 24/48 V DC (standard) DC-12: 3 A at 250 V DC (low level) DC-12: 3 A at 250 V DC (standard) DC-12: 6 A at 125 V DC (low level) DC-12: 6 A at 24/48 V DC (low level)
Minimum load	100 mA at 24 V 2 mA at 15 V

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty	18 months
----------	-----------
