



### Main

Range of product	Mureva Styl
Device presentation	Complete product
Colour tint	Grey (RAL 7016)

### Complementary

Device mounting	Surface
Switch function	2-way
Actuator	Rocker
Rated current	10 AX
Load type	Load for energy saving lamps with ballast: 100 W
[Ue] rated operational voltage	250 V AC
Local signalling	LED (blue)
Led current consumption	0.15 mA at 250 V
Condition of use	Indoor/outdoor
Material	SEBS ABS (acrylonitrile butadiene-styrene) Brass
Fixing mode	By screws
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> for rigid cable(s) 1.5...2.5 mm <sup>2</sup> for stranded cable(s) 1.5...2.5 mm <sup>2</sup> for flexible cable(s)
Wire stripping length	13 mm
Cable entry	Easy valve access diameter: 6...20 mm
Height	76 mm
Width	76 mm
Depth	64 mm
Projecting depth	64 mm

### Environment

Quality labels	AENOR EAC CE
----------------	--------------------

NF

IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	121 g
Package 1 Height	6.5 cm
Package 1 width	7.6 cm
Package 1 Length	7.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.31 kg
Package 2 Height	17 cm
Package 2 width	9 cm
Package 2 Length	40 cm
Unit Type of Package 3	S04
Number of Units in Package 3	60
Package 3 Weight	8.68 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information