



## Main

Range of product	Mureva Styl
Product or component type	Socket-outlet
Device presentation	Mechanism
Outlet poles configuration	2P + E with shutters
Outlet standard description	Pin earth
Outlet standard	French
Colour tint	Grey (RAL 7016)

## Complementary

Device mounting	Flush Surface
Rated current	16 A
Number of power socket outlets	1
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/outdoor
Material	Brass PP (polypropylene) PC (polycarbonate)
Fixing mode	By screws
Clamping connection capacity	1...2.5 mm <sup>2</sup> for rigid cable(s) 1...2.5 mm <sup>2</sup> for stranded cable(s) 1...2.5 mm <sup>2</sup> for flexible cable(s)
Wire stripping length	13 mm
Height	71 mm
Width	71 mm
Depth	47 mm

## Environment

Quality labels	NF
IP degree of protection	IP55
IK degree of protection	IK08

Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	62 g
Package 1 Height	4.5 cm
Package 1 width	7.1 cm
Package 1 Length	7.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	723 g
Package 2 Height	17 cm
Package 2 width	9 cm
Package 2 Length	40 cm
Unit Type of Package 3	S04
Number of Units in Package 3	60
Package 3 Weight	5.114 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information