Product data sheet Characteristics

ISM10200

OptiLine 45 - installation trunking - 95x55 mm - PVC - white - 2000 mm



Main

Range of product	OptiLine 45	
Cabling installation system	Trunking	
Product or component type	Installation trunking	
Colour tint	White (RAL 9010)	
Quantity per set	12 m	
Market segment	Residential Small commercial	

Complementary

Trunking material	Plastic	
Trunking dimension	95 x 55 mm	
Compartment partitioning	1 compartment	
Mounting location	Internal	
Fixing mode	By screws	
Front opening size	45 mm	
Material	PVC (polyvinyl chloride)	
Length	2000 mm	
Height	95 mm	
Width	55 mm	

Environment

Environment		# # # # # # # # # # # # # # # # # # #
Standards	73/23/EEC 93/68/EEC EN 50085-1:2005 EN 50085-2-1:2002 NF C 68-102	lended as a subsit
Ambient air temperature for operation	-2560 °C	not in
IP degree of protection	IP30	<u></u>
IK degree of protection	IK07	

Packing Units

Package 1 Weight	12.276 kg	

Package 1 Height	12.000 cm	
Package 1 width	30.000 cm	
Package 1 Length	203.300 cm	

Contractual warranty

Contraction warranty	
Warranty	18 months

ISM10200 is replaced by:



Trunking ISM10200P

OptiLine 45 - installation trunking - 95x55 mm - PVC - polar white - 2000 mm Qty 1

Reason for Substitution: End of life | Substitution date: 10 August 2017