



Main

| | |
|-----------------------------|------------------------|
| Range of product | OptiLine 45 |
| Cabling installation system | Trunking |
| Product type | Wall/ceiling frame |
| Colour | Polar white (RAL 9003) |
| Quantity package 1 / unit | Set of 1 |

Complementary

| | |
|--------------------|-------------|
| Trunking material | Plastic |
| Trunking dimension | 95 x 55 mm |
| Fixing mode | Snap-fitted |
| Product material | PC/ABS |
| Length | 22 mm |
| Height | 150 mm |
| Width | 82 mm |

Environment

| | |
|-------------------------|--|
| Standards | 73/23/EEC 93/68/EEC EN 50085-1:2005 EN 50085-1:2013/A1 EN 50085-2-1:2006 EN 50085-2-1:2011/A1 |
| Operating temperature | -25...60 °C |
| IP degree of protection | IP40 |
| IK degree of protection | IK07 |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.033 kg |
| Package 1 Height | 0.230 dm |
| Package 1 width | 0.900 dm |
| Package 1 Length | 1.500 dm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |