



ⓘ Discontinued

Main

Range of product	OptiLine 45
Cabling installation system	Trunking
Product or component type	Installation trunking
Colour tint	White (RAL 9010)
Quantity per set	12 m
Market segment	Residential Small commercial

Complementary

Trunking material	Plastic
Trunking dimension	140 x 55 mm
Compartment partitioning	2 compartments
Mounting location	Internal
Fixing mode	By screws
Front opening size	45 mm
Material	PVC (polyvinyl chloride)
Length	2000 mm
Height	140 mm
Width	55 mm

Environment

Standards	73/23/EEC 93/68/EEC EN 50085-1:2005 EN 50085-2-1:2002 NF C 68-102
Ambient air temperature for operation	-25...60 °C
IP degree of protection	IP30
IK degree of protection	IK07

Packing Units

Package 1 Weight	1559.000 g
------------------	------------

Package 1 Height	40.000 mm
Package 1 width	55.000 mm
Package 1 Length	1000.000 mm

Contractual warranty

Warranty	18 months
----------	-----------

ISM10300 is replaced by:



Trunking ISM10300P

OptiLine 45 - installation trunking - 140x55 mm - PVC - polar white - 2000 mm

Qty 1

Reason for Substitution: End of life | Substitution date: 10 August 2017