



⚠ Discontinued

Main

| | |
|-----------------------------|------------------|
| Range of product | OptiLine 45 |
| Cabling installation system | Trunking |
| Product type | T-piece |
| Colour | White (RAL 9010) |
| Quantity package 1 / unit | Set of 1 |

Complementary

| | |
|--------------------|---|
| Trunking material | Plastic |
| Trunking dimension | 165 x 55 mm 185 x 55 mm 140 x 55 mm |
| Fixing mode | Snap-fitted |
| Product material | PC/ABS |
| Length | 162 mm |
| Height | 52 mm |
| Width | 57 mm |

Environment

| | |
|-------------------------|--|
| Standards | 73/23/EEC 93/68/EEC EN 50085-1:2005 EN 50085-1:2013/A1 EN 50085-2-1:2006 EN 50085-2-1:2011/A1 |
| Operating temperature | -25...60 °C |
| IP degree of protection | IP30 |
| IK degree of protection | IK07 |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.040 kg |
| Package 1 Height | 0.520 dm |
| Package 1 width | 0.570 dm |

| | |
|------------------|----------|
| Package 1 Length | 1.620 dm |
|------------------|----------|

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

ISM10308 is replaced by:



Trunking ISM10308P

OptiLine 45 - T-piece - 140 x 55 mm - PC/ABS - polar white

Qty 1

Reason for Substitution: End of life | Substitution date: 10 August 2017
