



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKL XCKM
Associated body	ZCKMD39 ZCKL1 ZCKLD31H7 ZCKLD35H7 ZCKMD35 ZCKM1H7 ZCKM5 ZCKM1H29 ZCKLD39H7 ZCKM8H29 ZCKL5 ZCKM1 ZCKM8H7 ZCKLD37H7 ZCKL7H7 ZCKM6H29 ZCKM9H29 ZCKM5H29 ZCKMD35H7 ZCKM8 ZCKMD37H7 ZCKL7 ZCKLD39 ZCKMD37 ZCKL8 ZCKMD31 ZCKLD31 ZCKL1H7 ZCKMD35H29 ZCKM7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKM6H7
 ZCKM6
 ZCKL5H7
 ZCKM9
 ZCKL6
 ZCKL6H7
 ZCKM7H29
 ZCKM5H7
 ZCKMD31H7
 ZCKM7H7
 ZCKMD31H29
 ZCKLD37
 ZCKMD39H29
 ZCKL8H7
 ZCKMD39H7
 ZCKMD37H29
 ZCKLD35

Movement of operating head	Rotary
Type of operator	Roller lever spring return thermoplastic
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------