



### Main

Range of product	Performa
Product or component type	Mesh tray
Quantity per set	6 m

### Complementary

Shape	U-shape
Material	Steel (electro-zinc)
Atmospheric-corrosivity category	C1
Longitudinal wire diameter	4.9 mm
Transversal wire diameter	3.9 mm
Cable cross section	12328 mm <sup>2</sup>
Standards	EN/ISO 9227 DIN 4102-12 EN 50102 EN 12329 IEC 60068-2-75 IEC 61537
Length	3 m
Height	75 mm
Width	200 mm
Height compatibility	70 mm
Width compatibility	200 mm
Surface treatment compatibility	Electro-zinc

### Environment

Ambient air temperature for operation	-40...120 °C
IK degree of protection	IK10

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

Package 1 Weight	1.213 kg
Package 1 Height	7.000 cm
Package 1 width	20.000 cm
Package 1 Length	300.000 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------