



Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	550 mm outside:
Height	450 mm outside:
Depth	148 mm outside:
Nb of 18 mm modules per row	24
Nb of horizontal rows	2
Electrical insulation class	Double insulation Class II
Provided equipment	1 x identification label 1 x marking kit 1 x terminal block 1 x blanking plate strip
Type of door	Without

Complementary

Enclosure mounting	Surface
9 mm pitches	48
Total number of 18 mm modules	48
Power dissipation in W	67 W
[In] rated current	125 A
[Ui] rated insulation voltage	400 V
Type of rail	Multifix
Mounting plate description	Without mounting plate
Cable entry	Cable or tube Cut-out plates Trunking

Removable plates

Number of terminal blocks	1 earth (Quick) with 27 outgoing
Distribution block outgoing	2 x 25 mm ² for earth 24 x 6 mm ² for earth 1 x 50 mm ² for earth
Enclosure material	Back part: technoplastic Front face: technoplastic Back part: metal Front face: metal
Colour	Enclosure: white (RAL 9016) Front face: grey (RAL 7004)
Targeted country	Spain
Embedding depth	0 mm
Internal depth	120 mm

Environment

Fire resistance	Back part: 650 °C Front face: 650 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Environmental characteristic	Halogen free
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.6 kg
Package 1 Height	15.5 cm
Package 1 width	64 cm
Package 1 Length	54 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------