## Product data sheet Characteristics

# NSYCRN54250

Spacial CRN plain door w/o mount.plate. H500xW400xD250 IP66 IK10 RAL7035...





#### Main

IVIAIII		
Range	Spacial	
Product name	Spacial CRN	
Application	Multi-purpose	
Category	Compact enclosure	
Enclosure nominal height	500 mm	- N
Enclosure nominal width	400 mm	- - -
Enclosure nominal depth	250 mm	
Installation accessory type	Wall-mounting	4
Device composition	1 body 1 cable gland plate 1 door 1 lock	
Door type	Plain	1
Mounting plate description	Without mounting plate	5

#### Complementary

Sides made from a single folded section  Back welded with double profile forming a protected sealed area	
Front face: 1 door(s)	
Reversible (120 °)	
3 mm double-bar lock	
Standard	
Front	
Door by hinges Cable gland plate by screws	
Body: steel	
Epoxy-polyester powder	
Grey (RAL 7035)	
	Back welded with double profile forming a protected sealed area  Front face: 1 door(s)  Reversible (120 °)  3 mm double-bar lock  Standard  Front  Door by hinges Cable gland plate by screws  Body: steel  Epoxy-polyester powder

Standards	IEC 62208	
Product certifications	UL CUL	
Net weight	9.196 kg	

#### Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	9.196 kg	
Package 1 Height	52 cm	
Package 1 width	42 cm	
Package 1 Length	27 cm	

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	

#### Contractual warranty

Warranty	18 months