## Product data sheet Characteristics

# **NSYMDVR8**

Vertical aluminium rail, height 800mm. Packaging unit: 10 pieces.









#### Overview

	·§
Lead time	Usually Ships within 4 Weeks

#### Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or component type	Rail
Application	Multi-purpose
For enclosure nominal dimensions	-
Mounting support	Fixing nut
Range compatibility	Spacial S3D Spacial CRN Spacial S3X Thalassa PLM
Device composition	1 upright
Quantity per set	Set of 10
Material	Aluminium

#### Complementary

Lead time	Usually Ships within 4 Weeks	
Main		
Range	Spacial	
Accessory / separate part category	Mounting accessory	
Product or component type	Rail	
Application	Multi-purpose	
For enclosure nominal dimensions	-	
Mounting support	Fixing nut	
Range compatibility	Spacial S3D Spacial CRN Spacial S3X Thalassa PLM	
Device composition	1 upright	
•		
Quantity per set	Set of 10	
·	Set of 10 Aluminium	
Quantity per set  Material  Complementary  Fixing mode	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location	
Quantity per set  Material  Complementary	Aluminium	
Quantity per set  Material  Complementary  Fixing mode	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location 800 mm nominal:	
Quantity per set  Material  Complementary  Fixing mode  Height	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location  800 mm nominal: 739.3 mm real:	
Quantity per set  Material  Complementary  Fixing mode  Height  Width	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location  800 mm nominal: 739.3 mm real: 25 mm	
Quantity per set  Material  Complementary Fixing mode  Height  Width  Depth	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location  800 mm nominal: 739.3 mm real: 25 mm  15 mm	
Quantity per set  Material  Complementary Fixing mode Height  Width Depth Thickness Net weight  Packing Units	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location 800 mm nominal: 739.3 mm real: 25 mm 15 mm 2.5 mm	
Quantity per set  Material  Complementary  Fixing mode  Height  Width  Depth  Thickness  Net weight  Packing Units  Unit Type of Package 1	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location 800 mm nominal: 739.3 mm real: 25 mm 15 mm 2.5 mm	
Quantity per set  Material  Complementary Fixing mode Height  Width Depth Thickness Net weight  Packing Units	Screwed - screw type M8 - on backstuds of enclosure location  800 mm nominal: 739.3 mm real: 25 mm  15 mm  2.5 mm  0.23 kg	
Quantity per set  Material  Complementary  Fixing mode  Height  Width  Depth  Thickness  Net weight  Packing Units  Unit Type of Package 1	Aluminium  Screwed - screw type M8 - on backstuds of enclosure location  800 mm nominal: 739.3 mm real: 25 mm  15 mm  2.5 mm  0.23 kg	

#### **Packing Units**

		·
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	230 g	
Package 1 Height	0.8 cm	

Package 1 width	3.5 cm
Package 1 Length	74 cm

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	

#### Contractual warranty

Warranty	18 months
vvarianty	