

2 Piece FatMax® XL™ Demolition Driver Set Slotted / Pozidriv



- Split-proof handle - Ultra strong and resists hammer blows from "over-strike"
- Steel striking cap - Can be hit with hammer for extra tough screws
- Thru Tang Blade & Cap - Transfers energy from Hammer blow on the cap direct to the tip
- Shatter Resistant Bar - Reduced tip breakage – plus can be used as pry bar and chisel
- Smooth Dimpled panel - For added grip when used as a chisel or pry bar
- Soft Grip panels - For high torque and comfort

Code	Description	Packaging	Box quantity
0-67-551	2 Piece FatMax® XL™ Demolition Driver Set Slotted / Pozidriv(8mmX130 mm,Pozidriv 2ptX130mm)	X	6
9-67-551	2 Piece FatMax® XL™ Demolition Driver Set Slotted / Pozidriv(8mmX130 mm,Pozidriv 2ptX130mm)	-	8

STANLEY

MULTIBIT & PRECISION SCREWDRIVERS

VDE Insulated Screwdrivers

- Each screwdriver is tested individually up to 10,000 volts
- Anti-slip handle
- Electrically insulated screwdriver offering optimum safety up to 1,000 volts and compliant with VDE, GS and EN 60900 provisions



Code	Description	Packaging	Box quantity
0-65-965	75mm(L) and 2,5mm(Tip W) VDE INSULATED SCREWDRIVERS	X	6
65-966-22	3mm(Tip W) and 100mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
0-65-967	100mm(L) and 4mm(Tip W) VDE INSULATED SCREWDRIVERS	X	6
65-967-22	4mm(Tip W) and 100mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
0-65-968	125mm(L) and 5,5mm(Tip W) VDE INSULATED SCREWDRIVERS	X	1
65-968-22	5,5mm(Tip W) and 125mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
0-65-969	150mm(L) and 6,5mm(Tip W) VDE INSULATED SCREWDRIVERS	X	6
65-969-22	6,5mm(Tip W) and 150mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
65-970-22	8mm(Tip W) and 175mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
65-971-22	10mm(Tip W) and 200mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
65-972-22	PH0 and 60mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
0-65-973	PH1 and 170mm(L) VDE INSULATED SCREWDRIVERS	X	6
65-973-22	PH1 and 80mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
0-65-977	PZ1 and 80mm(L) VDE INSULATED SCREWDRIVERS	X	6
0-65-978	PZ2 and 100mm(L) VDE INSULATED SCREWDRIVERS	X	6
0-65-974	PH2 and 200mm(L) VDE INSULATED SCREWDRIVERS	X	1
65-974-22	PH2 and 100mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
65-975-22	PH3 and 150mm(L) VDE INSULATED SCREWDRIVERS	N/A	120