



## VDE Insulated Screwdrivers

- Each screwdriver is tested individually up to 10,000 volts
- Anti-slip handle
- Electrically insulated screwdriver offering optimum safety up to 1,000 volts and compliant with VDE, GS and EN 60900 provisions

Code	Description	Packaging	Box quantity
<b>0-65-965</b>	75mm(L) and 2,5mm(Tip W) VDE INSULATED SCREWDRIVERS	X	6
<b>65-966-22</b>	3mm(Tip W) and 100mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>0-65-967</b>	100mm(L) and 4mm(Tip W) VDE INSULATED SCREWDRIVERS	X	6
<b>65-967-22</b>	4mm(Tip W) and 100mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>0-65-968</b>	125mm(L) and 5,5mm(Tip W) VDE INSULATED SCREWDRIVERS	X	1
<b>65-968-22</b>	5,5mm(Tip W) and 125mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>0-65-969</b>	150mm(L) and 6,5mm(Tip W) VDE INSULATED SCREWDRIVERS	X	6
<b>65-969-22</b>	6,5mm(Tip W) and 150mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>65-970-22</b>	8mm(Tip W) and 175mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>65-971-22</b>	10mm(Tip W) and 200mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>65-972-22</b>	PH0 and 60mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>0-65-973</b>	PH1 and 170mm(L) VDE INSULATED SCREWDRIVERS	X	6
<b>65-973-22</b>	PH1 and 80mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>0-65-977</b>	PZ1 and 80mm(L) VDE INSULATED SCREWDRIVERS	X	6
<b>0-65-978</b>	PZ2 and 100mm(L) VDE INSULATED SCREWDRIVERS	X	6
<b>0-65-974</b>	PH2 and 200mm(L) VDE INSULATED SCREWDRIVERS	X	1
<b>65-974-22</b>	PH2 and 100mm(L) VDE INSULATED SCREWDRIVERS	N/A	12
<b>65-975-22</b>	PH3 and 150mm(L) VDE INSULATED SCREWDRIVERS	N/A	120