



### Main

Range of product	Ultra
Product or component type	90° bend
Device application	Cable distribution
Colour tint	White (RAL 9010)
Quantity per set	Set of 40
Market segment	Residential Small commercial

### Complementary

Trunking dimension	40 x 16 mm 40 x 40 mm 40 x 25 mm
Trunking material	Plastic
Fixing mode	Snap-fitted
Material	ABS thermoplastic enclosure
Height	41 mm
Width	60 mm
Depth	60 mm

### Environment

Environmental characteristic	Halogen free
Standards	EN 50085-1:2005 EN 50085-2-1:2006
Ambient air temperature for operation	-5...60 °C
IP degree of protection	IP40
IK degree of protection	IK07

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

Package 1 Weight	17.000 g
Package 1 Height	60.000 mm
Package 1 width	41.000 mm
Package 1 Length	60.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------