Product data sheet Characteristics

MGU3.207.18

Unica - pushbutton switch - 10 A, 250 VAC - 2 m - white





Main

TTIONIT		
Range	Unica	
Device application	Control	Ť
Product or component type	Switch	
Aesthetic name	Unica (standard aesthetic)	9 4 4
Device presentation	Mechanism	
Switch function	2-way	i d
Switch application	Roller blind	
Rated current	10 A at 250 V AC 50/60 Hz	:-
Actuator	Push-button	
Number of modules	2 modules	E
Fixing mode	Clip-in	
Cover plate colour tint	White	

Complementary

Contacts type and composition	1 C/O	-
Mechanical interlocking	Interlock between up/down	
[lu] rated interrupted current	2.5 A for motor	9
Opening distance	> 3 mm	<u>, </u>
Marking	Down UP	
Connections - terminals	Screwless terminals	į
Cable cross section	2.5 mm² flexible cable 2.5 mm² rigid cable	
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0.3	*
Electrical durability	40000 cycles, cos phi = 0.6	
Insulation resistance	> 5 MOhm at 500 V	
Dielectric strength	2000 V	
		· · · · · · · · · · · · · · · · · · ·

Material	ASA + PC: mechanism cover
Standards	EN 60669-1 LV directive
	EMC directive
Ambient air temperature for operation	2535 °C
Ambient air temperature for storage	050 °C
Embedding depth	22 mm
Depth	34 mm
Width	45 mm
Height	45 mm
Net weight	0.0382 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	UV resistant Liquid soap Window-cleaning fluid Acetone Ammonia Bleach Alcohol Petrol Oil
Environmental health and issues	Halogen free

Packing Units

r doming office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	38.6 g
Package 1 Height	4 cm
Package 1 width	6.6 cm
Package 1 Length	6.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	452.75 g
Package 2 Height	4.5 cm
Package 2 width	13.5 cm
Package 2 Length	33.5 cm
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Weight	2.046 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
nvironmental Disclosure Product Environmental Profile		

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Contractual warranty		
Warranty	18 months	