



Main

Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	2-way
Switch application	Roller blind
Rated current	10 A at 250 V AC 50/60 Hz
Actuator	Push-button
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	Aluminium

Complementary

Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[I _u] rated interrupted current	2.5 A for motor
Opening distance	> 3 mm
Marking	Down UP
Connections - terminals	Screwless terminals
Cable cross section	2.5 mm ² flexible cable 2.5 mm ² rigid cable
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 I _u , cos phi = 0.3
Electrical durability	40000 cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V

Material	ABS (acrylonitrile butadiene-styrene): mechanism cover
Standards	LV directive EMC directive EN 60669-1
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	45 mm
Height	45 mm
Net weight	0.0382 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Bleach Liquid soap Oil Acetone Ammonia UV resistant Window-cleaning fluid Alcohol Petrol
Environmental health and issues	Halogen free

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	38 g
Package 1 Height	4.5 cm
Package 1 width	6.5 cm
Package 1 Length	6.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	452 g
Package 2 Height	14 cm
Package 2 width	5 cm
Package 2 Length	34 cm
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Weight	5.888 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------
