



Main

Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	2-way
Switch application	Roller blind
Rated current	10 A at 250 V AC 50/60 Hz
Actuator	Rocker
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	Aluminium

Complementary

Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[I _u] rated interrupted current	2.5 A for motor
Opening distance	> 3 mm
Marking	UP Down
Connections - terminals	Screwless terminals
Cable cross section	2.5 mm ² flexible cable 2.5 mm ² rigid cable
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 I _u , cos phi = 0.3
Electrical durability	40000 cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V

Material	ABS (acrylonitrile butadiene-styrene): mechanism cover
Standards	EN 60669-1 EMC directive LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 mm
Depth	34 mm
Width	45 mm
Height	45 mm
Net weight	0.0351 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil Ammonia UV resistant Alcohol Window-cleaning fluid Petrol Acetone Liquid soap Bleach
Environmental health and issues	Halogen free

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	38 g
Package 1 Height	4 cm
Package 1 width	6.5 cm
Package 1 Length	6.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	450 g
Package 2 Height	14 cm
Package 2 width	5 cm
Package 2 Length	33 cm
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Weight	2.11 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------
