



## Main

Range of product	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Switch
Device presentation	Mechanism
Switch function	1-pole 2-way
Number of rocker	2
Device application	Control
Provided equipment	Internal power connection
Colour tint	Aluminium

## Complementary

Rated current	10 AX at 250 V AC 50/60 Hz
Electrical durability	10000 cycles
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	2 modules
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> rigid cable 0...2.5 mm <sup>2</sup> flexible cable
Material	ABS (acrylonitrile butadiene-styrene); mechanism cover
Fixing mode	Clip-in
Width	45 mm
Height	45 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	34 mm
Embedding depth	22 mm
Net weight	0.039 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EN 60669-1 LV directive EMC directive

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Environmental characteristic	Liquid soap Oil Acetone Alcohol Window-cleaning fluid Bleach Ammonia Petrol UV resistant
Environmental health and issues	Halogen free

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	40.4 g
Package 1 Height	4.2 cm
Package 1 width	6.1 cm
Package 1 Length	6.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	469.67 g
Package 2 Height	4.6 cm
Package 2 width	13.5 cm
Package 2 Length	33.3 cm
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Weight	2.186 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

---

Warranty	18 months
----------	-----------

---