



Main

Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device application	Communication
Device presentation	Mechanism with central plate
Colour tint	Aluminium
Data socket type	RJ45 4 contact(s) Cat.6 < 250 MHz
Provided equipment	Label holder Protective flap

Complementary

Communication network type	1000BASE-TX
Communication port protocol	ATM 1200 Mbps
Product destination	Floor box Duct
Number of modules	1 module
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	S/FTP
Organization of wire	Shielded twisted pair
Connections - terminals	Click
Device mounting	Flush
Fixing mode	Clip-in By clips: shield
Installation direction	Straight
Material	ABS (acrylonitrile butadiene-styrene): mechanism cover
Depth	36 mm
Width	22.5 mm
Height	45 mm
Embedding depth	25 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

IP degree of protection	IP40
IK degree of protection	IK01
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Environmental characteristic	Acetone Liquid soap Ammonia Alcohol Window-cleaning fluid Bleach Petrol Oil UV resistant
Environmental health and issues	Halogen free
Standards	ISO 8877

Packing Units

Package 1 Weight	0.045 kg
Package 1 Height	0.300 dm
Package 1 width	0.500 dm
Package 1 Length	0.500 dm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------