



Main

Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	SAT socket
Device presentation	Mechanism
TV socket type	Male individual
Colour tint	Aluminium

Complementary

SAT connector	Male IEC 9.52 mm
Path attenuation	11 dB TV signal5...2150 MHz
DC current flow	No
Number per line	1
Number of modules	2 modules
Material	ASA + PC: mechanism cover
Fixing mode	Clip-in
Depth	28 mm
Width	45 mm
Height	45 mm
Embedding depth	18 mm
Net weight	0.073 kg

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	15...35 °C
Ambient air temperature for storage	0...35 °C

Environmental characteristic	Acetone Ammonia UV resistant Liquid soap Window-cleaning fluid Alcohol Oil Petrol Bleach
Environmental health and issues	Halogen free
Standards	DIN 45325 EN 50083-1 UNE 20-523-79 (2e) EMC directive EN 50083-2 R.D. 279/1999 DIN 45330 R.D. 1/1998 EN 50083-4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	52 g
Package 1 Height	4.4 cm
Package 1 width	6.5 cm
Package 1 Length	6.7 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	638 g
Package 2 Height	14 cm
Package 2 width	5 cm
Package 2 Length	34 cm
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Weight	2.89 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------