# Product data sheet Characteristics

## MGU3.467.30

Unica Top/Class - TV single shield socket - female terminal - alu.



#### Main

Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	TV socket
Device presentation	Mechanism
TV socket type	Female terminal
Colour tint	Aluminium

#### Complementary

TV connector	Female IEC 9.52 mm	
Path attenuation	8 dB TV signal5862 MHz	
DC current flow	No	
Number per line	1	
Number of modules	2 modules	
Material	ASA + PC: mechanism cover	
Fixing mode	Clip-in	
Depth	28 mm	
Width	45 mm	
Height	45 mm	
Embedding depth	18 mm	
Net weight	0.073 kg	
·		<del></del> ,

#### Environment

IP degree of protection	IP20	a
IK degree of protection	IK01	nded
Ambient air temperature for operation	1535 °C	inte
Ambient air temperature for storage	035 °C	
Environmental characteristic	Window-cleaning fluid Liquid soap Alcohol Oil Bleach UV resistant	aimer: This documentation

	Ammonia Acetone Petrol
Environmental health and issues	Halogen free
Standards	EN 50083-2 EN 50083-1 EN 50083-4 EMC directive
Packing Units	
Package 1 Weight	52.000 g
Package 1 Height	67.000 mm
Package 1 width	38.000 mm
Package 1 Length	68.000 mm

### Contractual warranty

Warranty	18 months