



Main

Aesthetic name	Unica Top - Unica Class
Product or component type	Push-button dimmer
Device presentation	Mechanism
Fixing mode	Clip-in
Dimmer application	Inductive load Fan Resistive load
[Ue] rated operational voltage	230 V AC 50 Hz
Number of modules	2 modules
Cover plate colour tint	Aluminium

Complementary

Dimmer control	Impulse
Maximum permanent current	1.5 A
Total number of wires	3
Load type	230 V AC incandescent lamp - 20...250 W 230 V AC halogen lamp - 20...350 W Low voltage halogen lamp with ferromagnetic transformer - 20...350 VA Low voltage halogen lamps with toroidal transformer - 20...300 VA 230 V AC fan - 20...200 W 230 V AC convector - 20...350 W
Protection type	Electronic overvoltage protection Current protection
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	$\leq 2 \times 2.5 \text{ mm}^2$
Connected auxiliaries	Maximum 25 auxiliary switches Maximum 5 with light indication
Material	ASA + PC: mechanism cover
Standards	EN 60669-2-1
Product certifications	AENOR CE
Ambient air temperature for operation	5...30 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	47 mm
Width	45 mm
Height	45 mm
Net weight	0.078 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	UV resistant Alcohol Ammonia Petrol Oil Liquid soap Acetone Bleach Window-cleaning fluid
Environmental health and issues	Halogen free

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	98 g
Package 1 Height	6.5 cm
Package 1 width	9.5 cm
Package 1 Length	11 cm
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Weight	1.816 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------