



Main

Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	Movement detector
Device presentation	Mechanism
Load type	230 V AC incandescent lamp - 2300 W 230 V AC halogen lamp - 2000 W Low voltage halogen lamp with wire-wound transformer - 1500 VA Low voltage lamps with electronic transformer - 1150 VA 230 V AC fan - 200 VA 230 V AC convector - 2300 W 230 V AC contactor - 200 VA Fluorescent tube (diameter: 26...38 mm): 1 1-10 V dimmable electronic ballast - 2000 VA, cos phi = 0.9 Compact fluorescent lamp - 500 VA
Cover plate colour tint	Aluminium

Complementary

Power range	2300 W
[Ue] rated operational voltage	230 V AC +/- 10 % at 50/60 Hz
Movement detection area	10 x 20 m (PIR mounting height 2.15 m) 9 x 18 m (PIR mounting height 1.2 m)
Presence detection area	5 x 10 m (PIR mounting height 1.2 m) 6 x 12 m (PIR mounting height 2.15 m)
Detection angle	Full 180° Partial 90° left or right
Selection modes	M: manual S: slave A: automatic
Number of modules	2 modules
Type of setting	Adjustable disconnection time and brightness

Control type	Manual override with 5 push-buttons maximum
Wiring configuration	3 wires with neutral
Light intensity adjustment	5...1000 lux
Time delay range	2 s...20 min
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Marking	L+N
Connections - terminals	Screw terminals
Material	ASA + PC: mechanism cover
Fixing mode	Clip-in
Mounting height	1.2...2.15 m
Depth	58 mm
Width	45 mm
Height	45 mm
Embedding depth	34 mm
Net weight	0.076 kg

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-20...55 °C
Relative humidity	0...5 %
Environmental characteristic	Alcohol Oil Petrol Ammonia Acetone Window-cleaning fluid Liquid soap UV resistant Bleach
Environmental health and issues	Halogen free
Standards	EN 60669-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	109 g
Package 1 Height	6.5 cm
Package 1 width	9.8 cm
Package 1 Length	10.8 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty	18 months
----------	-----------
