



Main

Range of product	Unica
Aesthetic name	Unica KNX
Product or component type	Switch
Device presentation	Mechanism
Bus type	KNX
Switch function	1-pole 2-way
Number of rocker	2
Device application	Control
Colour tint	Aluminium

Complementary

Rated current	10 A at 24 V DC
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Actuator	Push-button
Number of modules	2 modules
Pilot light	LED, colour: blue, current consumption: 1 mA, temperature rise: 15 °C
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm ² rigid cable 0...2.5 mm ² flexible cable
Material	Plastic
Surface finish	Varnished
Device mounting	Flush
Fixing mode	Clip-in
Depth	38 mm
Embedding depth	13 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	-5...45 °C
Standards	EN 60669-1 LV directive EMC directive

Environment

IP degree of protection	IP20
Environmental characteristic	UV resistant Liquid soap Acetone Oil Petrol Alcohol Bleach Window-cleaning fluid Ammonia
Environmental health and issues	Halogen free

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	94 g
Package 1 Height	8 cm
Package 1 width	9.5 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Weight	2.87 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------