



### Main

Aesthetic name	Unica Top - Unica Class
Product or component type	Time delay switch
Device presentation	Mechanism
Cover plate colour tint	Aluminium

### Complementary

[Ue] rated operational voltage	230 V AC +/- 10 % at 50 Hz
Load type	230 V AC incandescent lamp - 1840 W 230 V AC halogen lamp - 1840 W 230 V AC fan - 600 W 230 V AC convector - 1840 W Low voltage halogen lamp with ferromagnetic transformer - 1840 VA Low voltage halogen lamp with electronic transformer - 1840 VA Fluorescent tube conventional ballast - 1840 VA Compact fluorescent lamp - 1840 W LED lamp Contactor - 200 W
Load interrupting current	8 A
Contacts type and composition	1 NO
Protection type	Current protection Electronic overvoltage protection
Time delay range	2 s...12 min
Number of modules	2 modules
Fixing mode	Clip-in
Pilot light	Neon locator lamp, colour: blue, current consumption: 1 mA, temperature rise: max +15 °C above ambient temperature
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 1 x 1.5 mm <sup>2</sup> for rigid cable(s)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Fuse type	Electronic
Connected auxiliaries	Maximum 25 auxiliary push-buttons Maximum 5 auxiliary push-buttons with light indication
Material	ASA + PC: mechanism cover
Depth	47 mm
Width	45 mm
Height	45 mm
Embedding depth	34 mm
Net weight	0.078 kg

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
Environmental characteristic	Oil Liquid soap Ammonia Window-cleaning fluid Acetone Bleach Petrol UV resistant Alcohol
Environmental health and issues	Halogen free
Product certifications	CE AENOR
Standards	EN 60669-2-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	103 g
Package 1 Height	6.3 cm
Package 1 width	9.7 cm
Package 1 Length	10.7 cm
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Weight	1.872 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

---

Warranty	18 months
----------	-----------

---