



ⓘ Discontinued

Commercial status

Discontinued on: 18 December 2018

End-of-service soon on: 11 October 2020

MGU3.559.18 has not been replaced. Please contact your customer care center for more information.

Main

Aesthetic name	Unica (standard aesthetic)
Product or component type	Rotary dimmer
Device presentation	Mechanism
Fixing mode	Clip-in
[Ue] rated operational voltage	127 V AC 50/60 Hz 230 V AC 50/60 Hz
Number of modules	1 module
Cover plate colour tint	White

Complementary

Dimmer control	ON/OFF push Level by turning knob
Total number of wires	2
Load type	127 V AC halogen lamp - 40...250 W 127 V AC incandescent lamp - 40...250 W 230 V AC halogen lamp - 60...400 W 230 V AC incandescent lamp - 60...400 W
Fuse type	4 Ah 5 x 20 mm 127 V 50/60 Hz 4 Ah 5 x 20 mm 230 V 50/60 Hz
Marking	L+N
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Material	ASA + PC: mechanism cover
Standards	IEC 60669-1, 1998-Ed.3 + A1, 1999 IEC 60669-2-1, 2002-Ed.4
Product certifications	CE NOM/ANCE
Ambient air temperature for operation	5...30 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for storage	-20...60 °C
Embedding depth	34 mm
Depth	50 mm
Width	22.5 mm
Height	45 mm
Net weight	0.09 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Alcohol Window-cleaning fluid UV resistant Liquid soap Acetone Petrol Ammonia Bleach Oil
Environmental health and issues	Halogen free

Packing Units

Package 1 Weight	90.000 g
Package 1 Height	65.000 mm
Package 1 width	87.000 mm
Package 1 Length	80.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------