



### Main

Range	Unica
Device application	Signalling
Product or component type	Electronic bell
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Aluminium

### Complementary

Current consumption	14 mA
Type of setting	5 programmable melodies
Connections - terminals	Screw terminals
Acoustic level	70 dB/1m
Cable cross section	0.75...1.5 mm <sup>2</sup> flexible cable 0.75...1.5 mm <sup>2</sup> rigid cable
Connected auxiliaries	3 indicator lights connected in parallel 10 standard push-buttons connected in parallel
Material	ASA + PC: mechanism cover
Standards	IEC 62080
Product certifications	CE
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	33 mm
Depth	44 mm
Width	45 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Height	45 mm
Net weight	0.11 kg

## Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Liquid soap Alcohol Acetone Window-cleaning fluid UV resistant Petrol Bleach Ammonia Oil
Environmental health and issues	Halogen free

## Packing Units

Package 1 Weight	0.146 kg
Package 1 Height	0.650 dm
Package 1 width	0.750 dm
Package 1 Length	0.850 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------