



Main

Range	Unica
Accessory / separate part category	Cabling accessory
Product or component type	Cable outlet
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Number of modules	2 modules
Fixing mode	Clip-in
Provided equipment	Anti-tug clamps
Colour tint	Aluminium

Complementary

Range compatibility	Unica
Rated current	16 A
Connections - terminals	Screw terminals
Clamping connection capacity	<= 3 x 2.5 mm ² for flexible cable(s) <= 3 x 2.5 mm ² for rigid cable(s)
Material	ASA + PC: mechanism cover
Product certifications	ES.ME01.B02319 AC CE EAC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Width	45 mm
Height	45 mm
Net weight	0.0178 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Environment

IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	Ammonia Liquid soap Petrol Bleach Oil Window-cleaning fluid Alcohol UV resistant Acetone
Environmental health and issues	Halogen free

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	21 g
Package 1 Height	4 cm
Package 1 width	6.5 cm
Package 1 Length	6.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	266 g
Package 2 Height	5 cm
Package 2 width	34 cm
Package 2 Length	14 cm
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Weight	1.324 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------